

Scholastic Pro 90

Engine-Off Pre-Conditioning | Supplemental Interior Heat | Eliminating Cold Starts



Coolant Heater Features:

- Auxilliary heating for school and shuttle buses of all sizes, offering up to 31,000 BTU/h (9.1 kW) of heating power
- Arctic Start function provides quick pre-heat even in extremely cold temperatures
- Low heater power consumption due to highly efficient design
- Highest product quality with long service life
- Automatic altitude adjustment up to 11,000 feet (3,350 m)
- Several mounting options available
- Quiet operation

Warm Weather Benefits:

- Reduce DPF maintenance costs
- Stops white smoke at start up
- Eliminates diesel knock
- Extend DPF regeneration cycles
- Reduce emissions

Cold Weather Benefits:

- Engine pre-heating
- Idle reduction
- Fuel savings
- Accelerated defrost
- Reduce engine wear

Technical specifications

	Scholastic Pro 90
Heating Capacity (Control range / Boost)	6,100 – 26,000 BTU/h / 31,000 BTU/h (<i>1.8 – 7.6 kW / 9.1 kW</i>)
Fuel Consumption (Control range / Boost)	0.05 – 0.23 gal/h / 0.29 gal/h (<i>0.2 – 0.9 l/h / 1.1 l/h</i>)
Fuels (Suitability for special fuels)	JP8, Diesel 1, Diesel 2, Arctic, Biodiesel (PME)
Rated Voltage	12 V
Power Consumption (Part load - full load / Boost)	37 – 83 W / 90 W
Operational Temperature Range	- 40° to +176° F (- 40° to +80° C)
Dimensions (L x W x H)	15 x 5.5 x 9.13 in (381 x 140 x 232 mm)
Weight	10.8 lbs (4.9 kg)

Technical specifications for circulating pump (attached to heater)

	U4840
Coolant Flow	3 gal/min (700 l/h)
Dimensions (L x W x H)	7.1 x 2.9 x 4.4 in (180 x 74 x 112 mm) including connectors
Weight	

Available Scholastic Pro 90 Heater Kit:

Scholastic Pro 90 Compact Kit w/ SmarTemp Control 3.0 P/N: 5013917

Standard Kit Contents:

- Heater w/ Mounting Bracket
- Electrical Harness
- Fuel System
- Exhaust System
- Installation Accessories
- SmarTemp 3.0
- Literature Pack

Included:

SmarTemp Control 3.0:

Part Number 5013873

- Same unit controls air or coolant heater
- Programmable run times (Timers)
- Adjustable Low Voltage Disconnect (LVD)
- Preventive maintenance reminder
- Heater fault codes displayed



Webasto Thermo & Comfort North America, Inc.

15083 North Road Fenton, Michigan 48430 USA Toll Free: 800-860-7866 Phone: 810-593-6000